



Contactors 4-pole

AC Operated

Ratings		Rated Current	Aux. Contacts		Type	Coil voltage ²⁾	Pack Weight pcs. kg/pc.	Wiring Diagram	
AC2 AC3	AC1		Built-in	Additional see page 46					
380V	AC1	690V A							
400V									
415V	400V								
kW	kW								
4	17,5	25	-	-	max. 4	MC10N-S-00-40	1	0,22	S00-40
4	17,5	25	-	-	MCA.. or	MC10N-S-00-22	1	0,22	
4	17,5	25	-	-	MCAH.	MC10N-S-00-04	1	0,22	
5,5	17,5	25	-	-		MC14N-S-00-40	1	0,22	S00-22
5,5	17,5	25	-	-		MC14N-S-00-22	1	0,22	
5,5	17,5	25	-	-		MC14N-S-00-04	1	0,22	
7,5	22	32	-	-		MC18N-S-00-40	1	0,22	S00-04
7,5	22	32	-	-		MC18N-S-00-22	1	0,22	
7,5	22	32	-	-		MC18N-S-00-04	1	0,22	
11	22	32	-	-		MC22N-S-00-40 ...	1	0,22	
11	31	45	-	-	max. 4	K2-23A00-40 ...	1	0,65	
15	34,5	50	-	-	MCA..	K2-30A00-40 ...	1	0,65	
18,5	34,5	50	-	-	or MCAH..	K2-37A00-40 ...	1	0,65	
22	55	80	-	-	max. 6	K2-45A00-40 ...	1	1,1	
30	69	100	-	-	-MCA. or MCAH..	K2-60A00-40 ...	1	1,1	



1) Other coil voltages on request

2) Coil voltage range and non-standard coil voltages on request

3) with integrated coil suppressor

4) other technical data on request