



REAR PANEL MOUNTING

PROTECTION CLASS EN60529 - IP65 UL50 NEMA TYPE 1-4-4X-12

12-16-20A	
25-32-40A	
63-80A	
125A	
200A	

SERIEs	AC21A	1 POLE	2 POLES	3 POLES	4 POLES
P012	12A	P0120008R	P0120009R	P0120010R	P0120011R
P016	16A	P0160008R	P0160009R	P0160010R	P0160011R
P020	20A	P0200008R	P0200009R	P0200010R	P0200011R
C025	25A	C0250008R	C0250009R	C0250010R	C0250011R
C032	32A	C0320008R	C0320009R	C0320010R	C0320011R
C040	40A	C0400008R	C0400009R	C0400010R	C0400011R
C063	63A	C0630008R	C0630009R	C0630010R	C0630011R
C080	80A	C0800008R	C0800009R	C0800010R	C0800011R
G125	125A	G1250008R	G1250009R	G1250010R	G1250011R
G200	200A	G2000008R	G2000009R	G2000010R	G2000011R

ACTUATOR	FIXING	P012 - P016 - P020	C025 - C032 - C040	C063 - C080	G125	G200
	screw	001/0008 056X/0008	007/0008	201/0008	441/0008	461/0008
	screw	002/0008 058X/0008	008/0008	-	-	-
	screw	003/0008 059X/0008	003/0008	-	-	-
	screw	004/0008 060X/0008	004/0008	-	-	-
	screw	009/0008 061X/0008	009/0008	209/0008	449/0008	449/0008
	screw	010/0008 062X/0008	010/0008	210/0008	450/0008	450/0008
	ø22	057X/0008-CA	-	-	-	-
	ø22	-	028X	-	-	-
	ø22	-	029X	-	-	-

UL50 NEMA Type 1-4-4X
 Key removable at "0" position
 Body mounting rotated by 90°
 Key removable at 0° and 180°