Pegasus

Emergency push buttons ø 22 EN ISO 13850

DESCRIPTION	COLOUR	CODE	WEIGHT gr	MIN. PACK QTY.	DIMENSIONS
Mushroom operator ø 30 twist to release	•	PPFN1R3N	42	10	32.6
Mushroom operator with vision ø 30 twist to release	•	PPFN1R3S	44	10	Ø 31 .
Mushroom operator ø 40 twist to release	•	PPFN1R4N	44	10	910
Mushroom operator with vision ø 40 twist to release	•	PPFN1R4S	46	10	Ø 40
Mushroom operator ø 60 twist to release	•	PPFN1R6N	50	10	Ø 60
Mushroom operator with vision ø 60 twist to release	•	PPFN1R6S	52	10	260

Pegasus

Emergency push buttons ø 22

EN ISO 13850



AUTOMATION TECHNOLOGIES

DESCRIPTION	COLOUR	CODE	WEIGHT gr	MIN. PACK QTY.	DIMENSIONS
Mushroom operator ø 40 with key release	•	PPFN1C4N	76	10	240
Mushroom operator ø 40 push-pull	•	PPFN1P4N	44	10	% 18 % 18 % 18
Mushroom operator ø 40 push-pull with vision	•	PPFN1P4S	46	10	940
Mushroom operator ø 40 push-pull with colour cap Mushroom operator ø 40 push-pull with lens cap	•	PPFN1P4C ————————————————————————————————————	45 45	10 ——— 10	40 ·

TECHNICAL NOTES

- All operators comply with the relevant European standard
- EN ISO 13850 Machine safety
 Emergency stop operators, functional characteristics Design guidelines
- | IEC/EN60947-5-1
 - Comply with the standard IEC/EN60204-1: Machine safety Machine electrical circuits General guidelines

The push buttons are designed with a load charge mechanism to ensure a reliable operation and stoppage, or blockage, in the activated position. The combination with positive switching NC

contacts and the presence of the "status" indicator on some models, guarantee a high degree of reliability and effectiveness.