

LOOM TUBE

Loom tube is a split corrugated conduit designed for quick, neat, cost effective wire harnessing or where flexible protection is required for cable connections, such as between cabinets and instruments mounted on hinged cabinet doors. The product is manufactured from black, flame retardant, polypropylene copolymer, with an operating temperature of -10 to 90 degrees celcius. RoHS Compliant.

Split Tubing

| CODE | PART NO. | ID mm | OD mm | COLOUR | LENGTH m |
|------|-----------|-------|-------|--------|----------|
| BA | LT7/10M | 7.0 | 10.4 | BLACK | 10 |
| | LT7/25M | 7.0 | 10.4 | BLACK | 25 |
| | LT7/50M | 7.0 | 10.4 | BLACK | 50 |
| | LT7/100M | 7.0 | 10.4 | BLACK | 100 |
| | LT7/400M | 7.0 | 10.4 | BLACK | 400 |
| | LT10/10M | 9.7 | 12.8 | BLACK | 10 |
| | LT10/30M | 9.7 | 12.8 | BLACK | 30 |
| | LT10/50M | 9.7 | 12.8 | BLACK | 50 |
| | LT10/100M | 9.7 | 12.8 | BLACK | 100 |
| | LT10/250M | 9.7 | 12.8 | BLACK | 250 |
| | LT13/10M | 12.6 | 15.7 | BLACK | 10 |
| | LT13/30M | 12.6 | 15.7 | BLACK | 30 |
| | LT13/50M | 12.6 | 15.7 | BLACK | 50 |
| | LT13/150M | 12.6 | 15.7 | BLACK | 150 |
| | LT16/10M | 16.3 | 20.9 | BLACK | 10 |
| | LT16/30M | 16.3 | 20.9 | BLACK | 30 |
| | LT16/50M | 16.3 | 20.9 | BLACK | 50 |
| | LT16/100M | 16.3 | 20.9 | BLACK | 100 |
| | LT20/10M | 21.1 | 25.2 | BLACK | 10 |
| | LT20/30M | 21.1 | 25.2 | BLACK | 30 |
| | LT20/50M | 21.1 | 25.2 | BLACK | 50 |
| | LT20/100M | 21.1 | 25.2 | BLACK | 100 |
| | LT23/50M | 23.0 | 27.0 | BLACK | 50 |
| | LT25/10M | 29.0 | 33.0 | BLACK | 10 |
| | LT25/30M | 29.0 | 33.0 | BLACK | 30 |
| | LT25/50M | 29.0 | 33.0 | BLACK | 50 |
| | LT36/25M | 36.0 | 42.0 | BLACK | 25 |
| | LT48/25M | 48.0 | 54.0 | BLACK | 25 |



LOOM TUBE



LOOM TUBE
INSTALLATION TOOL

Loom Tube Installation Tool

| CODE | PART NO. | DESCRIPTION | PACK QTY |
|------|----------|---|----------|
| TT | LTIT | ECONOMICAL, FAST AND SIMPLE TO USE TOOL | 1 |