## SPIROLL CABLE WRAPPING

Spiroll, spiral wrapping band is designed to bind and protect hoses, wires and cables in harnesses and wiring looms. Manufactured from either natural or black polyethylene, the material exhibits excellent electrical, abrasive and binding strength. Spiroll's flexible construction enables the easy routing of wiring looms. Due to the material's durability, the product is re-useable and has almost unlimited expansion. Depending on roll size and diameter, Spiroll is either supplied in specially designed dispenser boxes or plastic bag.

CODE	PART NO.	BUNDLE RANGE mm	COLOUR	ID mm	LENGTH mm
ВА	CTC3N	4–12	NATURAL	4	50
	СТСЗВ	4–12	BLACK	4	50
	CTC6N	6–50	NATURAL	6	50
	CTC6B	6–50	BLACK	6	50
	CTC12N	12–100	NATURAL	9	25
	CTC12B	12–100	BLACK	9	25
	CTC3N/10	4–12	NATURAL	4	10
	CTC3B/10	4–12	BLACK	4	10
	CTC6N/10	6–50	NATURAL	6	10
	CTC6B/10	6–50	BLACK	6	10
	CTC12N/10	12–100	NATURAL	9	10
	CTC12B/10	12–100	BLACK	9	10
	CTC19N/10	15–100	NATURAL	15	10
	CTC19B/10	15–100	BLACK	15	10
	CTC24N	20–130	NATURAL	20	10
	CTC24B	20–130	BLACK	20	10



**SPIROLL WRAPPING BAND** 


## **Heavy Duty Spiroll**

CODE	PART NO.	BUNDLE RANGE mm	COLOUR	ID mm	LENGTH mm
ВА	CTC12B - MT	12–100	BLACK	9	25
	CTC6B - MT	6–50	BLACK	6	50

## **QUIKFLEX SLEEVING**

Quikflex braided (or woven) sleeving from Carroll is a black, flexible, expanding harness medium, made from single filament polyester. The woven construction allows Quikflex to expand in diameter considerably to firmly harness wire lengths. Wires can also be poked through the sleeving, to enable harness breakouts.

CODE	PART NO.	DIAMETER mm	MINIMUM	MAXIMUM	LENGTH mm
ВА	QF3BK	3	1	6	100
	QF6BK	6	3	9	100
	QF10BK	10	7	19	100
	QF13BK	13	8	24	100
	QF19BK	19	14	30	100



**QUIKFLEX**