



AC Variable Speed Inverter Drives 0.4kW - 110kW (0.5HP - 150HP)



Feature **driven**

SD1

Comprehensively specified inverters for AC motors 0.4kW - 110kW (0.5HP - 150HP)

- Single-phase up to 2.2kW (3HP)
- Three-phase up to 110kW (150HP)
- Torque vector control
- STO (Safe Torque OFF) feature
- Integral Modbus-RTU / RS485
- Multiple filter options



SD1 AC Inverter Drives

The SD1 range is the ultimate variable speed drive for you! Easy to set up, and comprehensively specified for use in virtually any application, the SD1 is IMO's first complete range of variable speed drives which offer STO (SIL2 / SIL3) dependent upon model, along with a huge range of enhanced features, normally found on much more expensive inverter drives.

A range of EMC filter options makes the SD1 suitable for virtually every industrial, commercial or domestic application.

- IP20
- Torque Vector Control
- STO (Safe Torque OFF) - SIL2 / SIL3
- Up to 150% Starting Torque
- Front Mounted RJ45 Socket ($\leq 2.2\text{kW}/3\text{HP}$)
- Din Rail Mountable ($\leq 2.2\text{kW}/3\text{HP}$)
- Fixed Keypad with Potentiometer ($\leq 2.2\text{kW}/3\text{HP}$)
- Detachable Keypad ($\geq 4\text{kW}/5.5\text{HP}$)
- HDI Input (Pulse)
- 1/2 Analogue Inputs
- 1/2 Analogue Outputs
- 2 C/O Output Relays
- Transistor Output
- 4/5 Digital Inputs
- Selectable PNP/NPN I/O
- Integral Modbus-RTU / RS485
- PID Control as Standard
- DC Injection Braking
- Integral Brake Chopper ($\leq 30\text{kW}/40\text{HP}$)
- Motor Auto-tune (Static & Dynamic)
- Internal DC Reactor ($\geq 18.5\text{kW}/25\text{HP}$)
- Internal C3 Filter ($\geq 4\text{kW}/5.5\text{HP}$)
- Optional C3 Filter ($\leq 2.2\text{kW}/3\text{HP}$)
- Optional C1 & C2 Filter
- CE
- RoHS & Reach Compliant
- UL / cUL* / TUV
- 2 Year Warranty




* Approval pending.
Please check with IMO for current status

Safety As Standard

The SD1 is the first entry level range of variable speed drives from IMO which include Safe Torque OFF (STO) as standard. STO is a hugely important safety feature which could prevent industrial accidents and even save lives. But what exactly is STO?

The STO feature ensures that no torque-generating energy is put through the equipment. STO is used to bring the drive to a complete standstill, and also prevents any unexpected or unintentional starting of the motor or drive. It therefore enables safe working when for example, the protective door or cover is open or removed.

The advantage of an integrated STO functionality compared with standard safety solutions using electromechanical switchgear, is initially the elimination of multiple components and associated part failure and maintenance, but is also considerably quicker due to a shorter switching time than a conventional solution.



STO Benefits:

- Eliminates requirement for conventional solutions such as power cutting relay or contactor
- Reduces time and costs associated with wiring and maintenance

High Performance At Low Speeds

The SD1 range offers torque vector control across all models in the range. IMO is renowned for manufacturing market-leading variable speed drives and the Jaguar range has been long established with high-end features such as torque vector control, however the SD1 range heralds a new era in feature rich inverter drives due to the sheer array of standard features you would normally expect to find in considerably more expensive models.


The SD1 range delivers stable torque output even at low speeds, allowing the SD1 to be used in an even wider range of applications including lifts and conveyor systems, and high-inertia loads that demand a higher starting torque.

Enhanced Control Functionality


As you would expect, a drive from IMO isn't your average run-of-the-mill product. We produce solutions which tick every box, every time, and the SD1 is no different. From offering motor auto-tune which minimises power losses, to PID control which allows motor operation whilst controlling temperature, pressure and flow rate without the use of an external device or controller, together with the inclusion of programmable logic functionality, the SD1 is so packed with features that you wouldn't believe they fit inside its compact and user-friendly form.

Connected For Communications

Every model in the SD1 range offers communication capability. The connection is completed by way of twisted-pair to the dedicated RS-485 terminals found on the control terminal block - see diagram overlaid. Communications are carried out using the Modbus-RTU protocol.



SD1 Features



SD1 Application Examples

With the array of advanced features and filter options, the SD1 is suited for use in virtually any application, whether it be industrial, commercial or domestic. The following are examples of, but not limited to, the type of application where the SD1 can be employed:-



Fan Applications

- HVAC
- Water Treatment Plants
- Automatic Milking System



Pump Applications

- HVAC
- Waste Water
- Process Cooling



[Bottom View]

NOTE:
 0.4kW - 2.2kW (0.5HP - 3HP)
 External Filter
 4kW - 110kW (5.5HP - 150HP)
 Internal Filter


Fan hatch



Replaceable fan



EMC Filter (optional)



Note: For a more detailed control connections diagram, please refer to the SD1 technical datasheet found at www.imopc.com



Conveyor Applications

- Mining & Metals
- Logistics
- Food Machinery



Hoist Applications

- Cranes & Lifts
- RTG's
- Material Handling

The versatile and feature-rich SD1 is ideal for hundreds of different applications in all segments of industry

SD1 Ratings & Specifications

Single Phase 220Vac					
Model	Frame Size	Output Power	Input Current	Output Current	
SD1-2.5A-21	1	0.4kW	0.5HP	6.5A	2.5A
SD1-4.2A-21	1	0.75kW	1.0HP	9.3A	4.2A
SD1-7.5A-21	2	1.5kW	2.0HP	15.7A	7.5A
SD1-10A-21	2	2.2kW	3.0HP	24.0A	10.0A

Three Phase 220Vac					
Model	Frame Size	Output Power	Input Current	Output Current	
SD1-2.5A-23	2	0.4kW	0.5HP	3.7A	2.5A
SD1-4.2A-23	2	0.75kW	1.0HP	5.0A	4.2A
SD1-7.5A-23	3	1.5kW	2.0HP	7.7A	7.5A
SD1-10A-23	3	2.2kW	3.0HP	11.0A	10.0A
SD1-16A-23	3	4.0kW	4.5HP	17.0A	16.0A
SD1-20A-23	4	5.5kW	7.5HP	21.0A	20.0A
SD1-30A-23	4	7.5kW	10.0HP	31.0A	30.0A

Three Phase 380Vac					
Model	Frame Size	Output Power	Input Current	Output Current	
SD1-2.5A-43	2	0.75kW	1.0HP	3.4A	2.5A
SD1-4.2A-43	2	1.5kW	2.0HP	5.0A	4.2A
SD1-5.5A-43	2	2.2kW	3.0HP	5.8A	5.5A
SD1-9.5A-43	3	4.0kW	5.5HP	13.5A	9.5A
SD1-14A-43	3	5.5kW	7.5HP	19.5A	14.0A
SD1-18.5A-43	4	7.5kW	10.0HP	25.0A	18.5A
SD1-25A-43	4	11.0kW	15.0HP	32.0A	25.0A
SD1-32A-43	4	15.0kW	20.0HP	40.0A	32.0A
SD1-38A-43	5	18.5kW	25.0HP	47.0A	38.0A
SD1-45A-43	5	22.0kW	30.0HP	51.0A	45.0A
SD1-60A-43	6	30.0kW	40.0HP	70.0A	60.0A
SD1-75A-43	6	37.0kW	50.0HP	80.0A	75.0A
SD1-92A-43	7	45.0kW	60.0HP	98.0A	92.0A
SD1-115A-43	7	55.0kW	75.0HP	128.0A	115.0A
SD1-150A-43	7	75.0kW	100.0HP	139.0A	150.0A
SD1-180A-43	8	90.0kW	125.0HP	168.0A	180.0A
SD1-215A-43	8	110.0kW	150.0HP	201.0A	215.0A

Dimensions



Frame Size 1		
Height	Width	Depth
160mm (6¼")	80mm (3½")	123.5mm (4¾")



Frame Size 2		
Height	Width	Depth
185mm (7¼")	80mm (3½")	140.5mm (5½")



Frame Size 3		
Height	Width	Depth
256mm (10¼")	146mm (5¾")	167mm (6¾")

Frame Size 4		
Height	Width	Depth
320mm (12¾")	170mm (6¾")	196.3mm (7¾")



Frame Size 5		
Height	Width	Depth
340.6mm (13¾")	200mm (7¾")	184.3mm (7¼")

Frame Size 6		
Height	Width	Depth
400mm (15¾")	250mm (9¾")	202mm (8")



Frame Size 7		
Height	Width	Depth
560mm (22")	282mm (11¾")	238mm (9¾")

Frame Size 8		
Height	Width	Depth
554mm (21¾")	338mm (13¾")	329.2mm (13")

Note: Imperial measurements tolerance $\pm 1/4"$

Options & Ordering Codes

SD1	-	2.5A	-	21						
Series Code		Nominal Power (see Output Current)		Input & Phase						
				<table border="1"> <tr> <td>21</td> <td>220V Single Phase</td> </tr> <tr> <td>23</td> <td>220V Three Phase</td> </tr> <tr> <td>43</td> <td>380V Three Phase</td> </tr> </table>	21	220V Single Phase	23	220V Three Phase	43	380V Three Phase
21	220V Single Phase									
23	220V Three Phase									
43	380V Three Phase									

Optional External EMC Filters

Single Phase 220Vac

Model	C3 Filter / Current		C2 Filter / Current	
SD1-2.5A-21	SD1-RFC3-10	10A	SD1-RFC2-10	10A
SD1-4.2A-21	SD1-RFC3-10	10A	SD1-RFC2-10	10A
SD1-7.5A-21	SD1-RFC3-10	10A	SD1-RFC2-16	16A
SD1-10A-21	SD1-RFC3-10	10A	SD1-RFC2-16	16A

Three Phase 220Vac

Model	C3 Filter / Current		C2 Filter / Current	
SD1-2.5A-21	SD1-RFC3-7	7A	SD1-RFC2-6	6A
SD1-4.2A-21	SD1-RFC3-7	7A	SD1-RFC2-6	6A
SD1-7.5A-21	Internal	-	SD1-RFC2-16	16A
SD1-10A-21	Internal	-	SD1-RFC2-16	16A
SD1-16A-23	Internal	-	SD1-RFC2-32	32A
SD1-20A-23	Internal	-	SD1-RFC2-32	32A
SD1-30A-23	Internal	-	SD1-RFC2-45	45A

Three Phase 380Vac

Model	C3 Filter / Current		C2 Filter / Current	
SD1-2.5A-43	SD1-RFC3-7	7A	SD1-RFC2-6	6A
SD1-4.2A-43	SD1-RFC3-7	7A	SD1-RFC2-6	6A
SD1-5.5A-43	SD1-RFC3-7	7A	SD1-RFC2-6	6A
SD1-9.5A-43	Internal	-	SD1-RFC2-16	16A
SD1-14A-43	Internal	-	SD1-RFC2-16	16A
SD1-18.5A-43	Internal	-	SD1-RFC2-32	32A
SD1-25A-43	Internal	-	SD1-RFC2-32	32A
SD1-32A-43	Internal	-	SD1-RFC2-45	45A
SD1-38A-43	Internal	-	SD1-RFC2-45	45A
SD1-45A-43	Internal	-	SD1-RFC2-65	65A
SD1-60A-43	Internal	-	SD1-RFC2-65	65A
SD1-75A-43	Internal	-	SD1-RFC2-100	100A
SD1-92A-43	Internal	-	SD1-RFC2-100	100A
SD1-115A-43	Internal	-	SD1-RFC2-150	150A
SD1-150A-43	Internal	-	SD1-RFC2-150	150A
SD1-180A-43	Internal	-	SD1-RFC2-240	240A
SD1-215A-43	Internal	-	SD1-RFC2-240	240A

Accessories

Model	Description
SD1-KP	Remote Keypad
SD1-KP-CPY	Remote Keypad with Copy function
SD1-KP-MB	Keypad Mounting Bracket



SD1-KP

SD1-KP-MB