SPLIT LOOM TUBE - FLAME RETARDANT

Carroll's Quikcrimp loom tube is a split corrugated conduit designed for quick, neat, cost effective wire harnessing solution to consolidate loose wires into a wire loom, and protect them from damage caused from abrasion, heat and harsh environments.

It is also Flame Retardant using a halogenated flame retardant system to UL94 V2 rating. Also available with an enhanced UV stabilisation package, suitable for outdoor applications on request.

Australian manufactured, corrugated polypropylene tubing designed for cost-effective flexible protection in a wide range of automotive, marine and industrial applications.

Features:

- Excellent chemical resistant to automotive oils, fluids and solvents
- Extremely tough and durable, using a high impact copolymer polypropylene for enhance impact resistance
- Operating temperature range from -20°C to 90°C
- ROHS compliant



Split Tubing

PART NO.	ID mm	OD mm	COLOUR	LENGTH m
LT5/100M	5,0	8,0	BLACK	100
LT7/10M	7.0	10.4	BLACK	10
LT7/25M	7,0	10.4	BLACK	25
LT7/50M	7.0	10.4	BLACK	50
LT7/100M	7,0	10.4	BLACK	100
LT7/400M	7.0	10.4	BLACK	400
LT10/10M	9.7	12.8	BLACK	10
LT10/30M	9.7	12.8	BLACK	30
LT10/50M	9.7	12.8	BLACK	50
LT10/100M	9.7	12.8	BLACK	100
LT10/250M	9.7	12.8	BLACK	250
LT13/10M	12.6	15.7	BLACK	10
LT13/30M	12.6	15.7	BLACK	30
LT13/50M	12.6	15.7	BLACK	50
LT13/150M	12.6	15.7	BLACK	150
LT16/10M	16.3	20.9	BLACK	10
LT16/30M	16.3	20.9	BLACK	30
LT16/50M	16.3	20.9	BLACK	50
LT16/100M	16.3	20.9	BLACK	100
LT20/10M	21.1	25.2	BLACK	10
LT20/30M	21.1	25.2	BLACK	30
LT20/50M	21.1	25.2	BLACK	50
LT20/100M	21.1	25,2	BLACK	100
LT23/50M	23.0	27,0	BLACK	50
LT25/10M	29.0	33,0	BLACK	10
LT25/30M	29.0	33.0	BLACK	30
LT25/50M	29.0	33.0	BLACK	50
LT36/25M	36.0	42.0	BLACK	25
LT48/25M	48.0	54.0	BLACK	25





LOOM TUBE



LOOM TUBE INSTALLATION TOOL

Loom Tube Installation Tool

PART NO.	DESCRIPTION	PACK QTY
LTIT	ECONOMICAL, FAST AND SIMPLE TO USE TOOL	1











